

THE DIFFERENCE IS CLEAR

MARINE PRODUCT COMPARISON CHART

Effective Date: June 2020

ALL FCI WATERMAKERS SYSTEMS INCLUDE:

- Worldwide Support
- Non-proprietary Membranes
- Feed Pump

DIMENSIONSWidth without Membrane

Height

Depth without Membrane

Width with Membrane

Depth with Membrane

- 316SS HP Pump
- 316SS HP Fittings
- 5 micron Pre-filtration
- · Multiple Remote Station Capable
- Stage Starting

20.15 in / 511.81 mm

16.10 in / 408.94 mm

11.00 in / 279.40 mm

28.00 in / 711.20 mm

20.10 in / 510.94 mm

- TDS Monitoring
- · Automatically Diverts good water to the tanks
- Over Pressure Protection
- Loss of Prime Protection

- · Tank Level Control
- NEMA 4X Electrical Enclosure
- · Compact Small Footprint
- One-piece Aluminum Powder Coated Frame Construction

SERIES	AQUALITE	AQUAMISER+	MAX-Q+APC	MAX-Q+APC/DP	ATLAS+APC	ATLAS+APC/DP
GPD	200	250-1800	700-1850	SP (Single Pass): 1275-1850 DP (Double Pass): 900-1200 DTS (Dockside): 2000	1400-3600	SP (Single Pass): 2000-3600 DP (Double Pass): 1400-2500 DTS (Dockside): 2000
FEATURES						
Available in Modular Configuration		0	0		0	
Washdown Duty Feed Pump Motor		2	2	2	0	②
316SS Feed Pump Shaft		Q	2	②	0	0
40 sq. ft. Commercial Pre-filter		NC Upgrade	2	②	②	②
Washdown Duty Main Driver Motor		Q	0	2	②	©
4-point Vibration Isolation	②					
Dual-mount with 8-point Vibration Isolation		Q	Q	2	0	Q
316SS Pressure Vessel Ports	②	②	②	②	②	②
Upgradable		©	©	②	Q	Q
Exclusive AQ3 Control System	Q	Q				
Exclusive V4 Control System			0	2	Q	Q
Automatic Pressure Control (APC)			②	②	②	②
7" Marine Certified Touch Screen			©	②	Q	Q
Analog Flow Meters	0	Q				
Digital Flow Meters			Q	②	Q	Q
Analog Guages	Q	Q				
Digital Pressure Readout			0	2	0	0
Programmable Automatic Fresh Water Flush	Optional	Q	Q	0	Q	2
NMEA Compatible			Q	②	Q	0
MODBUS Ready			Q	0	Q	Q
On-Screen Help Menu			0	0	Q	Q
Dual Hertz Capable	Q	Q	0	Q	Q	Q
TDS Readout	w/ Remote	w/ Remote	0	0	0	2
Touch Pad Controls	②	Q				
Low Power Consumption	0					
Double Pass Spot-Free Water				Q		Q
Integrated DTS System				0		Q
3:1 Operational Modes				0		0
OPTIONS						
DTS Compatible		0	0		0	
Remote Stations	0	2	0	②	0	Q
Bridge Certified HMI Remote Station			0	0	2	0
pH Neutralizer	0	Q	0	0	2	2
Automated or Manual Media Filters		2	2	2	2	2
UV Sterilizer	0	0	0	2	0	0
DTS Feed Water Pressure Regulator				2		2
Filter Replacement Kit	0	Q	٥	0	Q	2

801.906.8840 FCIWATERMAKERS.COM

31.30 in / 789.94 mm

18.30 in / 464.82 mm

20.60 in / 523.24 mm

47.00 -54.70 in / 1193.80-1389.38 mm†

22.30 -24.30 in / 566.42-617.22 mm† 31.55 in / 801.37 mm

18.35 in / 466.09 mm

21.60 in / 548.64 mm

47.00 in / 1193.80 mm

23.25 in / 590.55 mm

31.30 in / 789.94 mm

18.30 in / 464.82 mm

20.60 in / 523.24 mm

47.00 -54.70 in / 1193.80-1389.38 mm†

22.30 -24.30 in / 566.42-617.22 mm† 25.00 in / 635.00 mm

15.30 in / 388.62 mm

17.00 in / 431.80 mm

47.15 in / 1197.61 mm

19.55 in / 496.57 mm † Depending on output / model

24.75 in / 628.65 mm

17.05 in / 433.07 mm

14.75 in / 374.65 mm

31.50-47.00 in / 800.10-1193.80 mm†

20.90 in / 530.86 mm